

**Tamper Resistance** Water Resistance

## **Analog HD Surveillance Cameras**

Protect Passengers, Deter Events and Capture Stunning Video Evidence

Build customizable, scalable and reliable safety solutions with REI. Ask about compatible cables, DVRs, fleet management software, hard drives, radios, monitors and accessories.



360° Split Screen



Down-the-Aisle



**Driver Side** 



**Stop-Arm Overview** 



**Passenger-Side Overview** 

Customize full coverage for your fleet vehicles. Contact your sales representative today.



## **AHD Color Cameras**

Eyeball	Mini Eyeball	Mini Dome	Mini Box	Windshield-Mount	Wedge	
		No.				





H: 85°-115° V: 46°-60°

2.8 mm-4 mm

IP67







H: 115° V: 60°

3.00" W

1.95" D

3.62" H

2.8 mm







710684 710685

H: 20° V: 12°

2.68" W

3.98" D

2.66" H



Fields of View - Horizontal & Vertical	H: 55°-115° V: 30°-60°	H: 170° V: 90°	
Sizes	3.39" W 3.31" D 3.12" H	Recessed: 2.68" W 2.5" D 2.0" H	Surface 2.32" W 2.32" D 2.16" H
True Wide Dynamic Range	•	•	•

True Wide Dynamic Range	•	•
1080p and 720p HD Resolution	•	• (710761 – 720p only)
Lens Equivalent/Focal Length	2.8 mm-6 mm	1.5 mm-1.8 mm
Day/Night Viewing	•	•

Proprietary Optimized Audio		710816 only
Adjustable Audio		
Optimized IR to Eliminate Hot Spots	710735 - no IR	•
Adjustable Camera Angle	•	•

IP67

Gorilla® Glass	•
Automatic Backlight Compensation	•
	Adapter cable required

	(round 6-pin to 4-pin Molex)
tes:	5" Pedestal-Mount Kit available
	IR not needed when windshield mounted

Adapter cable required for 710761 (round 4-pin to 4-pin Molex) 360° Camera Observation System

IP65

(optional for 710761) May be recessed for midship or above-aisle use

Camera: 3.44" W 4.53" W 2.19" D 2.17" H 2.78" H

Bracket: 3.56" W 1.36" D 2.36" H

710714, 710716, 710813

H: 55°-180° V: 30°-92°

IP65

IR not available on

IR not available on windshield-mount camera

Adapter cable required (round 6-pin to 4-pin Molex)

IP68